



Associated Security Services Ltd
Making your security our priority

AsSec Bulk Transfer Unit

Manual

This unit is manually operated via a side lever to control the interlocking doors, which prevent them from being opened at the same time.

It is designed for the transfer of bulk items i.e. cash in transit cash boxes, from a non—secure area to a secure area.

Reversible—The handling of the doors can be changed by turning the unit through 180 degrees.

This unit can be installed through counters and external and internal walls (up to 330mm thick without modification), at any convenient height. The front face of the unit has a flange which masks irregular edges of openings in the wall and which are designed to dissipate energy onto the surrounding wall in the event of a physical attack to the outer door. When lowered they become convenient shelves from which to lift heavy containers into or out of the unit.



Product Specification

Dimensions (mm)

Overall: 658(l) x 538(w) x 440(h)

Weight: 60kg

Aperture: 490(w) x 390(h)

Construction Body: 3mm mild steel

Doors: 1.5mm steel with a central core of bullet resistant armour

Finish: Charcoal grey polyester powder coating to 8-4734816; the outer skin of the external door is brushed stainless steel

Electrical: 240V, 13Amp, 50/60Hz; 12v battery back-up giving 12 hours emergency use

Electronic



Designed for the transfer of bulk items i.e. cash in transit cash boxes, from a non—secure area to a secure area

Comes complete with a sliding shelf installed to ease the transaction of large /heavy items

Designed and tested to meet ballistic attack BS 5051 part 1(G2/S86), BS EN 1522 (FB4/FSG)

Both come with optional extra of a support leg frame