



# AsSec Telescopic Security Posts

## Convenient Security

The telescopic security post offers a highly secure and convenient method of physical access control and general protection. The inner post simply raises vertically and locks in the upright position with an integral push button lock, providing a convenient way of securing most sites. Unlike removable bollards they do not need to be taken away to be stored and once in the lowered position with the lid lowered there is no trip hazard.

The 'residential version' is ideally suited to domestic applications being a scaled down version of the standard post.

A stainless steel version is also available in a standard brushed matte finish.

### Specifications

Heavy-duty re-enforced version available with a square or round inner.

All major components 'hot dipped' galvanised to BSEN ISO 1461 (1999).

High security 'anti-drill' lock push button action lock, with 500K key combinations.

Available finished in specific RAL or B.S Polyester and Nylon coatings.

High visibility retro-reflective bands can be fitted as an optional extra.



BT.LRR



BT.HDR



BT.SST



BT.RER



BT.HDS  
Heavy duty square finished in white



Most of the range has 'Sold Secure' approval as recommended by major insurance companies.

Please contact us for further details.

Post Type	Product Code	Rising Post Inner Diameter (mm)	Rising Post Inner Height (mm)	Below Ground (mm)	Inner Post Wall Thickness (mm)	Post Operating Weight kg
Residential	BT.RER	76	500	700	4	6
Standard Round	BT.STR	90	670	950	5	9
Standard Square	BT.STS	90 * 90	670	950	5	9
Heavy Duty Round	BT.HDR	90	670	950	8.3	11
Heavy Duty Square	BT.HDS	90 * 90	670	950	8.3	11
Stainless Steel Post	BT.SST	101	710	1050	5	17
Large Round	BT.LRR	114	850	1110	5	17